

WORLD INTELLECTUAL PROPERTY ORGANIZAT



INTEDNIA TONI

(5) Interval I ONAL APPLICATION PUBLISH	HED UNDER THE PATENT COOPERATION T	DEATY MAT
(51) International Patent Classification 7:	The state of the s	ALATT (PCT)
•	1 (11) T-4::	

(11) International Publication Number: WO 00/52780 H01M 8/12 (43) International Publication Date: 8 September 2000 (08,09,00)

(21) International Application Number: PCT/US00/05735

(22) International Filing Date: 3 March 2000 (03.03.00)

09/261,324 3 March 1999 (03.03.99) US

(63) Related by Continuation (CON) or Continuation-in-Part (CIP) to Earlier Application US 09/261,324 (CIP) Filed on 3 March 1999 (03.03.99)

(71) Applicant (for all designated States except US): GAS RE-SEARCH INSTITUTE [US/US]; 8600 West Bryn Mawr Avenue, Chicago, IL 60631 (US).

(72) Inventors; and

0) Priority Data:

(75) Inventors/Applicants (for US only): GORTE, Raymond, J. [US/US]; 512 Broad Acres Road, Narberth, PA 19072 (US). VOHS, John, M. [US/US]; 45 Sawgrass Lane, Newtown Square, PA 19073 (US). CRACIUN, Radu [US/US]; 3426 Bailey Creek Cove, South Collierville, TN 38109 (US).

(74) Agents: FEJER, Mark, E. et al.; Pauley Petersen Kinne & Fejer, Suite 365, 2800 West Higgins Road, Hoffman Estates, IL 60195 (US).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SL, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published


With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: METHOD FOR SOLID OXIDE FUEL CELL ANODE PREPARATION

(57) Abstract

A method for preparation of an anode for a solid oxide fuel cellin which a plurality of zircon fibers are mixed with a yttria-stabilized zirconia (YSZ) powder, forming a fiber/powder mixture. The fiber/powder mixture is formed into a porous YSZ layer and calcined. The calcined porous YSZ layer is then impregnated with a metal-containing salt solution. Preferred metals are Cu and Ni. anode and a method for manufacturing a fuel cell containing such anode is also disclosed. Such anode is particularly performant when the fuel cell is fed with dry hydrocarbons, in absence or low content of steam.



EXPRESS MAIL NO. <u>EL 815 472 76805</u>

MAILED.

YSZd = dense YSZ YSZp = porous YSZ

 \square , $\frac{p}{mox} = 5.1 \text{ mW/cm}^2$

o .Pmax = 19.4 mW/cm² \triangle , Procx = 34.6 mW/cm²

 $\frac{P_{\text{max}}}{2} = 4.0 \text{ mW/cm}^2$